

GVIS 300

Indirect Viewing Aid

Video Inspection Scope





The GVIS 300 from Greenlee eliminates the need to place the users hand in the same position each time to attain effective focus control. To inspect the backplane connector the user simply inserts the probe into the connector bulkhead. To focus simply turn the entire probe ½ to ½ a turn for complete focus range. No longer is it necessary for the user to keep one hand on the focus wheel.

The connector end face is displayed on a bright 3.5 inch LCD display and precision optics to provide an unmatched FOV (field of view) of $630\mu m$ by $440\mu m$.

Extended use Lithium Ion batteries provide 8-10 hours of continuous use. The battery can be charged in 3 hours using the "smart AC charger" (included). The GVIS 300 can continue to be used whilst charging.

A 2.5mm Universal Connector and SC Bulkhead Adaptor are provided as standard. Optional tips for the most commonly used connectors are available.

The GVIS 300 Monitor and Probe are supplied with separate carry cases. Also included is a battery charger, User Guide, cleaning Pen and Square.

For digital archiving of the connector end-face the GVCM 410 Video Capture Module allows quick storage of the image to any Windows based computer.

Features

- · Unique external focus mechanism eliminates need for "focus wheel"
- ¾ µm scratch resolution
- Thin (less than 1" dia.) ergonomic probe design
- · Quick change adapter tips for all connector styles
- 3.5 inch LCD Display
- FOV 630μm X 440μm
- Advanced Li Ion Battery & smart technology AC charger system
- Rugged and compact size
- Optional GVCM 410 USB 2.0 Video Capture Module for digital archiving of the image

Specification

| FOV (Field of View) | FOV 630µm x 440µm |
|----------------------------------|--|
| Resolution | ¾ micron |
| Light Source | Blue LED |
| Lighting Technique | Coaxial |
| Display screen size | 3.5 in diagonal |
| Battery Life | 8 to 10 hours continuous |
| Battery charge time | 3 hours |
| Size | Probe – 180mm x 25mm x 19mm Monitor – 120mm x 89mm x 32mm |
| Weight - (monitor, probe & case) | 0.54kg |
| Operating Temp. | 0° to 50 °C |
| Storage Temp. | -40°C to 70 °C |





Ordering Information

| MODEL | ORDER # | DESCRIPTION | QTY |
|---------------------------------------|----------|---|-----|
| GVIS 300 MP Video Inspection Scope | 52056253 | GVIS 300 Monitor and Probe, 601C Carry Case, SC Bulkhead and 2.5mm Universal Adaptor Tips, Battery Charger, Cleaning Pen and Square (requires additional Carry Case) | 1 |
| GVIS 300 MP (USB) | 52056254 | GVIS 300 Monitor with USB option, Probe, 601C Carry Case, SC Bulkhead and 2.5mm Universal Adaptor Tips, Battery Charger, Cleaning Pen and Square (requires additional Carry Case) | 1 |
| GVCM 410 | 52056255 | USB Video Capture Module | 1 |
| GVIS 300 P | 52056256 | GVIS 300 Probe, 601C Carry Case, Instructions and 2.5mm Universal Adaptor Tip | 1 |

Adaptor Tips for GVIS 300 Probe:

| GAC040 | 52056257 | SC Bulkhead | 1 |
|--------|----------|----------------------------|---|
| GAC041 | 52056258 | SC/APC Bulkhead | 1 |
| GAC042 | 52056259 | FC Bulkhead | 1 |
| GAC044 | 52056261 | LC Bulkhead | 1 |
| GAC046 | 52056263 | ST Bulkhead | 1 |
| GAC048 | 52056265 | 1.25mm Connector Universal | 1 |
| GAC049 | 52056266 | 2.5mm Connector Universal | 1 |

Messkom Vertriebs GmbH,

Distributed by:

Awarenring 38, D 85419 Mauern,

Tel.: 08764-9484-30, Fax: -33

Email: info@messkom.de,

URL: www.messkom.de





www.greenlee.com

4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070 ©2010 Greenlee Textron Inc. Greenlee Textron Inc. is a subsidiary of Textron Inc.