



technical data

FIBERLAUNCH ECO

The Fiberlaunch ECO is a new development of an easy to use Fiber Optic launch cable on an economic price level but with best quality

It is available for all kinds of connectors and fibres (OS2, OM1, OM2, OM3 and OM4) up to 1000m

We provide the ECO also as High Quality Version with steel armoured cables

The ECO is magnetic, so it holds on every metal part like 19" racks. Also customizing with your own logo is available.

To each assembled Fiberlaunch ECO we provide a measurement protocol (IL,RL)



FIBERLAUNCH ECO	SINGLEMODE	MULTIMODE
length	100m - 1000m	100m - 500m
fiber	Corning SMF 28 Ultra ITU-T: G.652.D G.657.A1	Corning Infinicore OM1, OM2, OM3, OM4
wavelength	1310nm - 1650nm	850nm, 1300nm
attenuation/km	max. -0,3dB	max.-0,9dB
connector	SC, LC, E2000, FCPC - also in APC	SC, LC, ST, FCPC
attenuation/connector	IL < -0,15 dB RL UPC >50dB, APC >65dB	ILdB < 0,20dB RL >30dB
mating cycles	min. 1000 cycles	min. 1000 cycles



purchase information

ECO-XX-XXX-XX/X-XX/X-XXX

type

ST = Standard PVC cables
 HQ = High Quality steel cables

fiber

OS2 = SM
 OM1 = 62,5/125
 OM2 = 50/125
 OM3 = OM3
 OM4 = OM4

polish
 A = APC

connector A

FC = FC-PC
 SC = SC
 LC = LC
 E2 = E2000
 ST = ST


polish
 A = APC

connector B

FC = FC-PC
 SC = SC
 LC = LC
 E2 = E2000
 ST = ST

length

100 = 100m
 150 = 150m
 200 = 200m
 300 = 300m
 500 = 500m
 1000 = 1000m



Also available: Hard carry case for 6 pcs. ECO
 Order Code: FL-HCC

Copyright 2015
 All rights are reserved by PH PALDEN GmbH
 „Fiberlaunch“ and Logo are a registered Trademark of PH PALDEN GmbH

Messkom Vertriebs GmbH
 Awareriring 38
 D-85419 Mauer

Tel: 0049 (0)8764 / 948 430
 Fax: 0049 (0)8764 / 948 433

Email: info@messkom.de



www.messkom.de

