# **AT8L** LAN TONER

The LAN Toner is designed for the network installation and maintenance professional and can be used on any wiring system including datacom, telecom, security/alarm, audio and CATV.

## FEATURES:

- Blinks HUB, Switch Port, and PC activity lights for fast identification
- Detect LAN hubs & switches
- Provides tone signaling, continuity testing and telephone line polarity indication combined with a modular breakout adatper

## ADVANTAGES:

- Selectable tone outputs for identifying multiple cable runs, easily set up “unbalanced” tone for easier detection
- Includes multiple connection options (RJ45 plug plus alligator clips)




## SPECIFICATIONS:

| | | | | |
|---|---|---|---|---|
| **ELECTRICAL** | | | | |
| Output Power (into 600Ω) | 8dBm | | | |
| Output Frequency (nominal) | Tracing Tone | | Warbling Tone | |
| | Tone 1 | 820/1110 Hz | Tone 1 | 1.9 Hz |
| | Tone 2 | 577/820 Hz | Tone 2 | 5.5 Hz |
| Voltage Protection | 60VDC | | | |
| **POWER SOURCE** | | | | |
| Battery | 9 VDC, alkaline recommended | | | |
| Battery Life | 50 hours | | | |
| **ENVIRONMENT** | | | | |
| Operating Temperature | 0°C to +70°C | | | |
| Storage Temperature | -25°C to +85°C | | | |
| Relative Humidity (max) | 80% | | | |
| **PHYSICAL** | | | | |
| Length | 117.8 mm | | | |
| Width | 52.5 mm | | | |
| Depth | 30.5 mm | | | |

## ORDERING INFORMATION:

| CAT. NO. | DESCRIPTION |
|---|---|
| AT8L | LAN tone generator |
| AT8LK | LAN toner kit (200EP probe and 700C carry case) |


1390 Aspen Way Vista, CA • 92081 TC-AT8L 07/21

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927050


©2021 Tempo Communications Inc. • An ISO 9001 Company


EMEA Office: Tempo Europe Limited
Brecon House • William Brown Close • Cwmbran • NP44 3AB • UK

*TempoCom.com | tel 800.642.2155 | sales@tempocom.com*


TEMPO® COMMUNICATIONS

***Renewed** Vision. **Innovation** Forward.*

Follow us on Social Media
**@TempoComms**